




# DH-4,8

Technisches Datenblatt

NOVASTAR A5S PLUS RECEIVINGCARD  
HIGH-BRIGHTNESS  
HIGH-CONTRAST  
QUICK-LOCK-SYSTEM  
MAGNETIC FAST-RIGG  
100% FRONT- & BACKSERVICE



# Festinstallation

<b>Pixelpitch</b>	4,8 mm
<b>Helligkeit</b>	6.000 nit
<b>SMD-Typ</b>	Nationstar Refond 1921 3-in-1 RGB
<b>SMD Merkmale</b>	High-Brightness, High-Contrast, High-Level
<b>Farbtiefe</b>	Bis zu 14 Bit
<b>Auflösung</b>	128 x 128   128 x 256 Pixel
<b>LED Treiberchip</b>	ICND2153
<b>Receivingcard</b>	Novastar A5S Plus
<b>Scantyp</b>	1/8
<b>Refreshrate</b>	≥ 3.840 Hz
<b>Horiz. Blickwinkel</b>	+75°/-75°
<b>Vert. Blickwinkel</b>	+55°/-55°
<b>Kontrast</b>	> 3.400:1
<b>Nennleistung</b>	Typisch 170 W/m <sup>2</sup>   max. 680 W/m <sup>2</sup>
<b>Spannungsbereich</b>	AC 210-240V/ 50 Hz
<b>Stromanschluss</b>	Seetronic
<b>Abmessungen (BxHxT)</b>	500 x 500   500 x 1.000   T=80 mm
<b>Gewicht</b>	30 kg/m <sup>2</sup>
<b>IP Klasse</b>	IP65 (Front & Back)
<b>Temperaturbereich</b>	Im Betrieb: -10°C bis + 40°C Lagernd: -10°C bis + 45°C
<b>Produkthighlights</b>	Quick-Lock-System, Magnetic Fast-Rigg, 100% Front- & Backservice
<b>Zertifizierungen</b>	   EMC