




# Frontfix fX-2,6 indoor

## Technisches Datenblatt

HIGH-BRIGHTNESS  
HIGH-CONTRAST  
BLACK-BODY  
FRONT- & REARSERVICE  
FULL & HALF PANELS



<b>Pixelpitch</b>	2,6 mm
<b>Helligkeit</b>	1.000 nit
<b>SMD-Typ</b>	Nationstar SMD2020
<b>SMD Merkmale</b>	High-Brightness, High-Contrast, Black-Body
<b>Farbtiefe</b>	13 Bit
<b>Auflösung</b>	384 x 192   192 x 192 Pixel (Full   Half)
<b>LED Treiberchip</b>	ICN2053
<b>Receivingcard</b>	A7S
<b>Scantyp</b>	1/16
<b>Refreshrate</b>	1.920-3.840 Hz
<b>Horiz. Blickwinkel</b>	+160°/-160°
<b>Vert. Blickwinkel</b>	+160°/-160°
<b>Kontrast</b>	5.000:1
<b>Nennleistung in W</b>	Typ. 226W   113W Max. 600W   300W (Full   Half)
<b>Spannungsbereich</b>	AC 220V/ 50 Hz
<b>Stromanschluss</b>	Neutrik powerCON
<b>Abmessungen (BxHxT)</b>	1000x500x83 mm   500x500x83 mm (Full   Half)
<b>Gewicht</b>	13,5 kg   7,5 kg (Full   Half)
<b>IP Klasse</b>	IP40 / IP21 (Front/ Rückseite)
<b>Temperaturbereich</b>	Im Betrieb: 0°C bis +60°C Lagernd: -40°C bis +55°C
<b>Produkthighlights</b>	Front- & Rearservice, Full & Half Panels
<b>Zertifizierungen</b>	   EMC