



vP2+ V1

Technisches Datenblatt

500 x 500 mm

BROMPTON R2 RECEIVINGCARD
 COLOR MATCHING TOOL
 1-6° CONCAVE
 HIGH-LEVEL
 BLACK-FACE
 QUICK-LOCK-SYSTEM
 MAGNETIC FAST-RIGG
 FAST REPLACEABLE BACKBOX



| | |
|----------------------------|---|
| Pixelpitch | 2,60 mm |
| Helligkeit | ≥ 1.200 nits |
| Gewicht | 8,5 kg |
| Nennleistung | Typisch 44 W max. 130 W |
| SMD-Typ | LEDitgo BF1515 |
| SMD Merkmale | Black-Face, High-Level |
| Farbtiefe | Bis zu 16 Bit |
| Auflösung | 192 x 192 px |
| LED Treiberchip | MBI5264 |
| Receivingcard | Brompton R2 |
| Scantyp | 1/24 |
| Refreshrate | ≥ 3.840 Hz |
| Horiz. Blickwinkel | +140° -140° |
| Vert. Blickwinkel | +140° -140° |
| Kontrast | > 5.500:1 |
| Spannungsbereich | AC 88-264V 50-60 Hz |
| Stromanschluss | Neutrik powerCON |
| Abmessungen (BxHxT) | 500 x 500 mm T = 80 mm |
| IP Klasse | IP 40 Front & Back |
| Temperaturbereich | -30°C bis +45°C (Im Betrieb) -10°C bis +55°C (Lagernd) |
| Produkthighlights | 1-6° Konkave Installation, Color Matching Tool, Magnetic Fast-Rigg, Fast Replacable Backbox |
| Zertifizierungen |     |