

TX1,5-C

Technisches Datenblatt

600 x 337,5 mm

COB TECHNOLOGY
NOVASTAR A10S PRO RECEIVINGCARD
5G READY
DRIVER ICND1069



Pixelpitch	1,56 mm
Helligkeit	≥ 1.200 nits
Gewicht	4,8 kg
Nennleistung	Typisch 31 W max. 90 W
LED-Typ	COB 1,56
LED Merkmale	High Brightness, High Contrast, High Level
Farbtiefe	Bis zu 14 Bit
Auflösung	384 x 216 px
LED Treiberchip	ICND1069
Receivingcard	Novastar A10S pro
Scantyp	1/54
Refreshrate	≥ 3.840 Hz
Horiz. Blickwinkel	+160° -160°
Vert. Blickwinkel	+140° -140°
Kontrast	> 10.000:1
Spannungsbereich	AC 210-240V 50-60 Hz
Stromanschluss	Seetronic
Abmessungen (BxHxT)	600 x 337,5 x 40 mm
IP Klasse	IP 41
Temperaturbereich	-20°C bis +50°C (Im Betrieb) -10°C bis +40°C (Lagernd)
Produkthighlights	COB Technologie, Novastar A10S Pro Receivingcard, 5G Ready

Zertifizierungen



Stand: 03/2025