

TX1,8E

Technisches Datenblatt

600 x 337,5 mm

SMD TECHNOLOGY
NOVASTAR A8S-N RECEIVINGCARD
NOVASTAR DRIVER ICND2153S



Pixelpitch	1,87 mm
Helligkeit	≥ 1.000 nits
Gewicht	4,8 kg
Nennleistung	Typisch 31 W max. 90 W
LED-Typ	SMD1212
LED Merkmale	High Brightness, High Contrast, High Level
Farbtiefe	Bis zu 14 Bit
Auflösung	320 x 180 px
LED Treiberchip	ICND2153S
Receivingcard	Novastar A8S-N
Scantyp	1/30
Refreshrate	≥ 3.840 Hz
Horiz. Blickwinkel	+140° -140°
Vert. Blickwinkel	+140° -140°
Kontrast	> 8.000:1
Spannungsbereich	AC 210-240V 50-60 Hz
Stromanschluss	Seetronic
Abmessungen (BxHxT)	600 x 337,5 x 40 mm
IP Klasse	IP 41
Temperaturbereich	-20°C bis +50°C (Im Betrieb) -10°C bis +40°C (Lagernd)
Produkthighlights	Novastar A8S-N Receivingcard, SMD-Technologie

Zertifizierungen



Stand: 03/2025