

RA193ix Flex

Technisches Datenblatt

496 x 496 mm

NOVASTAR A10S PRO RECEIVINGCARD
URT TECHNOLOGY
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
CURVING UP TO +/- 45°



Pixelpitch	1,93 mm
Helligkeit	≥ 800 - 1.000 nits
Gewicht	9,3 kg
Nennleistung	Typisch 48 W max. 200 W
LED-Typ	GOB
LED Merkmale	High-Level, Black-Face
Farbtiefe	22 Bit
Auflösung	256 x 256 px
LED Treiberchip	CFD955
Receivingcard	Novastar A10s Pro
Scantyp	1/32
Refreshrate	≥ 3.840 Hz
Horiz. Blickwinkel	+160° -160°
Vert. Blickwinkel	+160° -160°
Kontrast	> 6.000:1
Spannungsbereich	AC 100-240V 50 Hz
Stromanschluss	Seetronic TR1
Abmessungen (BxHxT)	496 x 496 x 55 mm
IP Klasse	IP 40
Temperaturbereich	-15°C bis +40°C (Im Betrieb) -20°C bis +45°C (Lagernd)
Produkthighlights	in Stufen 0, 2.5, 5, 7.5, 10, 12.5, 15, 17.5, 20 und 22.5 Grad konkav und konvex bei seitig einstellbar, minimaler Durchmesser von 1,27m
Zertifizierungen	   