

vM2.6 Pro V1

Technisches Datenblatt

Z500 x 500 mm

NOVASTAR A10S PRO RECEIVINGCARD
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
LIGHT-WEIGHT



Pixelpitch	2,60 mm
Helligkeit	≥ 1.300 nits
Gewicht	8,3 kg
Nennleistung	Typisch 45 W max. 140 W
Netzteilkapazität	300 W
LED-Typ	SMD1515
LED Merkmale	High-Level, Black-Face
Farbtiefe	16 Bit
Auflösung	192 x 192 px
LED Treiberchip	MBS7253
Receivingcard	Novastar A10s Pro
Scantyp	1/16
Refreshrate	≥ 7.680 Hz
Horiz. Blickwinkel	+140° -140°
Vert. Blickwinkel	+140° -140°
Kontrast	> 8.600:1
Spannungsbereich	AC 100-240V 50 Hz
Stromanschluss	Seetronic TR1
Abmessungen (BxHxT)	500 x 500 x 80 mm
IP Klasse	IP 40
Temperaturbereich	-15°C bis +40°C (Im Betrieb) -20°C bis +45°C (Lagernd)
Produkthighlights	Quick-Lock-System, Magnetic Fast-Rigg, Curving bis zu +/-5° in 2,5° Schritten
Zertifizierungen	   